



Basic Fit Harness

- Conforms and tested to OSHA 1926 Subpart M and ANSI Z359.1-2007
- Lightweight and comfortable for all day use
- NEW D-ring pad for added comfort
- Grommet legs
- One of the most affordable harnesses on the market
- 2-color design makes donning the harness easier

708858-1: S/M (34 in. – 44 in. waist)
708858-2: L/XL (42 in. – 50 in. waist)
708858-3: XXL (48 in. – 56 in. waist)



Constructor Harness

- Conforms and tested to OSHA 1926 Subpart M and 1910.66 Appendix C, ANSI Z359.1-2007 and A10.32-2004, and CSA Z259
- Ideal for steel erectors and riggers
- NEW breathable mesh material on shoulder pads for cooler more comfortable wear
- NEW covering over labels on chest strap protects from paint overspray or catching on hazards
- Grommet legs

708859-1: S/M (34 in. – 44 in. waist)
708859-2: L/XL (42 in. – 50 in. waist)
708859-3: XXL (48 in. – 56 in. waist)





Lanyards

Every personal fall arrest system requires a high-quality lanyard as a critical link between the anchorage and the harness. To ensure worker safety, Power Climber lanyards are manufactured with the highest-quality components available.

- Conforms to OSHA 1926 Subpart M and 1910.66 Appendix C, ANSI Z359.1-2007 and A10.32-2004, and CSA Z259
- Heavy-duty webbing with tamper-resistant locking snap hooks
- Quality workmanship
- Comfortable design that enhances maneuverability
- 310 lb load limit



Double lock snap hook




Form hook



Ladder hook

	6 ft shock-absorbing web lanyard	6 ft internal shock-absorbing web lanyard
Double lock snap hook	708861-1	708860-1
Form hook	708861-2	708860-2
Ladder hook	708861-3	708860-3



Safety Line

Power Climber's safety line is a combination fiber rope with excellent wear and high strength to weight. The balanced rope construction offers the durability of polyester ropes and higher strengths than those of other combination ropes. The 5/8 in. safety line meets or exceeds the requirements of OSHA 1926 Subpart M and ANSI A10.14 at the time of shipment, and is ANSI Z359.1-2007 compliant.

- 704076-1: per ft
- 704076-600: 600 ft on a spool
- 704076-1200: 1200 ft on a spool

